

3RK3111-1AA10

Industrial automation components

Manufacturer	Siemens
Catalog number	3rk3111-1aa10
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.11 kgs
Product ID	3RK3111-1AA10
Notes	Wycofanie produktu od: 01.10.2021 następcą 3SK2, S7-1200F lub ET200SP w przypadku stosowania AS-i
AL Field	N
Customs Tariff Code	85371098
Compliance	Produkt zgodny z RoHS od: 28.05.2009
Configurable Product	False
Country of Origin	DE
EAN	4011209684195.0
ECCN	EAR99
eClass 6	27-37-18-19
eClass 7.1	27-37-18-19
eClass 8	27-37-18-19
eClass Version 9	27-37-18-19
eClass Version 9.1	27-37-18-19
ETIM 7	EC001449
Group Classification Key	R711
List of Characteristics	CC-IC10
Quantity in Package	1
Packaging Length	133,00
Packaging Width	52,50
Packaging Height	133,00
Packaging Size	MM
Product Description	3RK3 PRZEKAŹNIK BEZPIECZEŃSTWA PROGRAMOWALNY, MODUŁ PODSTAWOWY 4/8 F-DI, 1F-R0, 1 F-D0, 24V DC, SPEŁNIA KATEGORI WG: EN- 954 KATEGORIA 4; IEC 61508 - SIL 3; ISO 13849-1 - PL e; ZACISKI ŚRUBOWE
Product Code	5358
Comparative Metals Coefficient	28.05.2009
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236
Unit of Measure	ST
UPC	754554961927.0

Description

3RK3111-1AA10 | Siemens, Basic Central Unit, 24 V dc, Yellow, 111 x 45 x 124 mm | Brand / Manufacturer: Siemens | height: 133 | width: 52 | depth: 133 | mass: 0.3 | product type: Basic Central Unit | supply voltage: 24 V dc | level of security: IP20 | Colour: Yellow | Size: 111 x 45 x 124 mm | operating temperature range: -20 to +60 °C | requirements met: CCC Certified;CSA Certified;UL Listed;EAC Certified;C-Tick Marked | period of operation: 10000000 cycles