

### 3RM1102-3AA04

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rm1102-3aa04
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.31 kgs
<b>eClass 7.1</b>	27-37-09-05
<b>eClass 8</b>	27-37-09-05
<b>eClass Version 9</b>	27-37-09-05
<b>eClass Version 9.1</b>	27-37-09-05
<b>ETIM 7</b>	EC001037
<b>Group Classification Key</b>	R711
<b>List of Characteristics</b>	CC-IC10
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	109,00
<b>Packaging Width</b>	36,00
<b>Packaging Height</b>	167,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	bezpieczny rozrusznik bezpośredni, 3RM1, 500 V, 0,09 - 0,75 kW, 0,4 - 2 A, DC 24 V, przyłącze śrubowe/sprężynowe (Push-in)
<b>Product Code</b>	3762
<b>Comparative Metals Coefficient</b>	01.03.2017
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236
<b>Unit of Measure</b>	ST
<b>UPC</b>	887621775575.0
<b>Product ID</b>	3RM1102-3AA04
<b>AL Field</b>	N
<b>Customs Tariff Code</b>	85371098
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.03.2017
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>EAN</b>	4011209935945.0
<b>ECCN</b>	N
<b>eClass 6</b>	27-37-09-05