

### 3RQ3018-2AB01

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rq3018-2ab01
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	0.45 kgs
Product ID	3RQ3018-2AB01
AL Field	N
Customs Tariff Code	85364190
Compliance	Produkt zgodny z RoHS od: 25.03.2015
Configurable Product	False
Country of Origin	TN
EAN	4047621000916.0
ECCN	N
eClass 6	27-37-16-01
eClass 7.1	27-37-16-01
eClass 8	27-37-16-01
eClass Version 9	27-37-16-01
eClass Version 9.1	27-37-16-01
ETIM 7	EC001437
Group Classification Key	R711
List of Characteristics	CC-IC10
Quantity in Package	1
Packaging Length	96,00
Packaging Width	80,00
Packaging Height	42,00
Packaging Size	MM
Product Description	Sprzęg wyjściowy 1 zestaw przełączny pozłacany utwardzany AC/DC 24 V szerokość obudowy 6,2 mm przyłącze sprężynowe (Push-in) prąd termiczny 6A
Product Code	4950
Comparative Metals Coefficient	25.03.2015
Unit of Measure	ST
UPC	804766215193.0

## Description

3RQ3018-2AB01 | Siemens, Output Coupler Relay, 24 V ac/dc, 6 A, 1C0, 0.3 W, 6.2 x 72.5 x 93 mm | Brand / Manufacturer: Siemens | product type: Output Coupler Relay | current rating: 6 A | supply voltage: 24 V ac/dc | power classification: 0.3 W | voltage on terminals: Push In | type of attachment: Snap On Mount | number of contacts: 1 | contact configuration: 1C0 | contact material: AgSn02-HTV | switch configuration: 1C0