

3RT10566NF36

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3rt10566nf36 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Legacy / discontinued |

Technical specification

| | |
|--------------------------------|--|
| Weight | 3.18 kgs |
| Product ID | 3RT1056-6NF36 |
| AL Field | N |
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85364900 |
| Compliance | Produkt zgodny z RoHS od: 01.05.2012 |
| Configurable Product | False |
| Copper Weight | 0 |
| Country of Origin | DE |
| EAN | 4011209507616.0 |
| ECCN | N |
| eClass 6 | 27-37-10-03 |
| eClass 7.1 | 27-37-10-03 |
| eClass 8 | 27-37-10-03 |
| eClass Version 9 | 27-37-10-03 |
| eClass Version 9.1 | 27-37-10-03 |
| ETIM 7 | EC000066 |
| Group Classification Key | R711 |
| List of Characteristics | CC-IC10 |
| Metals Coefficient | LF0----- |
| Quantity in Package | 1 |
| Packaging Length | 129,00 |
| Packaging Width | 190,00 |
| Packaging Height | 181,00 |
| Packaging Size | MM |
| Product Description | STYCZNIK, 90KW/400V/AC-3 AC/DC ZNAMION. NAP. STERUJĄCE UC 96-127V STYKI POM. 2NO+2NC 3-P, WLK. S6 PRZYŁĄCZE SZYNOWE NAPĘD ELEKTRONICZNY DO WYJŚCIA SPS 24 V DC |
| Product Code | 3706 |
| Comparative Metals Coefficient | 01.05.2012 |
| REACH | Lead CAS-Nr. 7439-92-1 |
| Unit of Measure | ST |
| UPC | 754554773681.0 |

Description

Power contactor, AC-3 185 A, 90 kW / 400 V AC (50-60 Hz) / DC operation 96-127 V UC
Auxiliary contacts 2 NO + 2 NC 3-pole, Size S6 Busbar connections Drive: electronic with
PLC interface 24 V DC screw terminal