

3RT10642NP36

Industrial automation components

Manufacturer	Siemens
Catalog number	3rt10642np36
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85364900
Copper Weight	0
eClass 6	27-37-10-03
eClass 7.1	27-37-10-03
eClass 8	27-37-10-03
eClass Version 9	27-37-10-03
eClass Version 9.1	27-37-10-03
Quantity in Package	1
Packaging Length	196,00
Packaging Width	265,00
Packaging Height	234,00
Product Code	3706
Comparative Metals Coefficient	01.05.2012
UPC	195125254534.0
Weight	6462 kg
Product ID	3RT1064-2NP36
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	Germany
ECCN	N
ETIM 7	EC000066
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LF0-----
Packaging Size	MM
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236; Lead titanium zirconium oxide lblREACHCasNo0830
Unit of Measure	ST
Product Description	Power contactor, AC-3 225 A, 110 kW / 400 V AC (50-60 Hz) / DC operation 200-277 V UC Auxiliary contacts 2 NO + 2 NC 3-pole, Size S10 Busbar connections Drive: electronic with PLC interface 24 V DC Spring-type terminal
EAN	4011209582477

Package Size Unit of Measure	Inch
Quantity Unit	1 Piece
Voltage Rating	400 V, 277 V, 24 V
Frequency Range	50 - 60 Hz
Article Number	3RT10642NP36
Product Family	SIRIUS 3RT contactors, 3-pole, up to 250 kW
Product Group	3706
Catalog ID	CC-IC10
Net Weight	14.246 lb
Packaging Dimensions	10.433 x 7.717 x 9.213
Packaging Quantity	1 pieces
Commodity Code	85364900
Current Rating	225 A
Power	110 kW
Number of Poles	3
Utilization Category	AC-3

Description

The SIRIUS 3RT contactor is designed for industrial applications, featuring a rated power of 110 kW at 400 V. It includes 3 poles and auxiliary contacts 2NO+2NC. The control voltage ranges from 200-277 V AC/DC, and its design allows for rail mounting. The product complies with RoHS and REACH standards, ensuring environmental safety. The net weight is 14.246 kg, with packaging dimensions of 10.433 x 7.717 x 9.213 inches.