

### 3RT1065-2AP36

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rt1065-2ap36
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85364900
Copper Weight	0
EAN	4011209582521.0
Quantity in Package	1
Product Code	3706
UPC	804766788772.0
Weight	6500
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	DE
ECCN	N
eClass 6	27-37-10-03
eClass 7.1	27-37-10-03
eClass 8	27-37-10-03
eClass Version 9	27-37-10-03
eClass Version 9.1	27-37-10-03
Product ID	3RT1065-2AP36
AL Field	N
ETIM 7	EC000066
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LF0-----
Packaging Length	196,00
Packaging Width	265,00
Packaging Height	234,00
Packaging Size	MM
Product Description	STYCZNIK, 132 KW / 400 V /AC-3 AC/DC ZNAMION. NAP. STERUJĄCE UC 220-240 V STYKI POM. 2N0+2NC 3-P, WLK. S10 PRZYŁĄCZE SZYNOWE - NAPĘD KONWENC., PODŁ CAGE CLAMP.
Comparative Metals Coefficient	01.05.2012
REACH	Lead CAS-Nr. 7439-92-1
Unit of Measure	ST

## Description

Power contactor, AC-3 265 A, 132 kW / 400 V AC (50-60 Hz) / DC operation 220-240 V UC  
Auxiliary contacts 2 NO + 2 NC 3-pole, Size S10 Busbar connections Drive: conventional  
Spring-type terminal