

### 3RT1065-6AB36-3PA0

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 3rt1065-6ab36-3pa0               |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

## Technical specification

|                                |   |
|--------------------------------|---|
| UPC                            | 887621221072.0  |
| Weight                         | 6600  |
| Aluminium Weight               | 0   |
| Argent Weight                  | 0   |
| Customs Tariff Code            | 85364900  |
| Copper Weight                  | 0   |
| EAN                            | 4011209936744.0   |
| Quantity in Package            | 1   |
| Product Code                   | 3706  |
| Metals Coefficient             | LF0-----  |
| Packaging Length               | 196,00  |
| Packaging Size                 | MM  |
| Packaging Width                | 265,00  |
| Packaging Height               | 234,00  |
| Product ID                     | 3RT1065-6AB36-3PA0  |
| AL Field                       | N   |
| Compliance                     | Produkt zgodny z RoHS od: 01.05.2012  |
| Configurable Product           | False   |
| Country of Origin              | DE  |
| ECCN                           | N   |
| eClass 6                       | 27-37-10-03   |
| eClass 7.1                     | 27-37-10-03   |
| eClass 8                       | 27-37-10-03   |
| eClass Version 9               | 27-37-10-03   |
| eClass Version 9.1             | 27-37-10-03   |
| ETIM 7                         | EC000066  |
| Group Classification Key       | R711  |
| List of Characteristics        | CC-IC10   |
| Product Description            | stycznik mocy, AC-3e/AC-3 265 A, 132 kW / 400 V AC (50-60 Hz) / DC Uc: 23-26 V 3-bieg., zestyki pomocnicze 2 NO + 2 NC zamontowany na stałe napęd: konwencjonalny obwód główny: szyna obwód sterowniczy i pomocniczy: przyłącze śrubowe |
| Comparative Metals Coefficient | 01.05.2012  |
| REACH                          | Lead CAS-Nr. 7439-92-1  |
| Unit of Measure                | ST  |