

### 3RT10656AD36

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rt10656ad36
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

eClass 7.1	27-37-10-03
eClass 8	27-37-10-03
eClass Version 9	27-37-10-03
eClass Version 9.1	27-37-10-03
Quantity in Package	1
Packaging Length	196,00
Packaging Width	265,00
Packaging Height	234,00
Product Code	3706
Comparative Metals Coefficient	01.05.2012
UPC	754554772479.0
Weight	6566 kg
Product ID	3RT1065-6AD36
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	DE
ECCN	N
ETIM 7	EC000066
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LF0-----
Packaging Size	MM
Product Description	STYCZNIK, 132KW/400V/AC-3 AC/DC ZNAMION. NAP. STERUJĄCE 42-48V UC STYKI POM. 2NO+2NC 3-P, WLK. S10 PRZYŁĄCZE SZYNOWE - NAPĘD KONWENCJ.
REACH	Lead CAS-Nr. 7439-92-1
Unit of Measure	ST
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85364900
Copper Weight	0
EAN	4011209507906.0
eClass 6	27-37-10-03

## Description

Power contactor, AC-3 265 A, 132 kW / 400 V AC (50-60 Hz) / DC operation 42-48 V UC  
Auxiliary contacts 2 NO + 2 NC 3-pole, Size S10 Busbar connections Drive: conventional  
screw terminal