3RT10656NF36

Industrial automation components

Add to quote

Ask about this product



Manufacturer	Siemens
Catalog number	3rt10656nf36
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Contact Rating (Current)	265 A
Contact Form	3PST-NO (3 Form A)
Coil Voltage	96–127 V AC/DC
Coil Power	580 W
Mounting Type	Chassis Mount, DIN Rail

Description

The Siemens 3RT10656NF36 is a robust power contactor designed for industrial applications requiring reliable motor switching. This 3-pole contactor is rated for AC-3e/AC-3 operation at 265 A and 132 kW for 400 V AC (50-60 Hz), and is also suitable for DC operation with a control voltage range of 96-127 V.

It features two normally open (NO) and two normally closed (NC) auxiliary contacts, providing versatile control options. The contactor is equipped with electronic drive technology and offers a PLC input with a 24 V DC control voltage, facilitating seamless integration into automated systems.

Its mounting options include chassis mount and DIN rail, ensuring flexible installation in various setups. The main circuit utilizes busbar connections, while the auxiliary circuit employs screw terminals, simplifying wiring processes.

This contactor is part of Siemens' SIRIUS 3RT series, known for its high performance and reliability in motor control applications.

Automation Trader
960 Capability Green
Luton, Bedfordshire LU1 3PE
VAT ID: PL6463009354
REGON: 527345886
DUNS: 427734105
BDO: 000726360

Phone
+44 7418 359 399

Email
info@automationtrader.com

Generated on demand. The PDF file is not stored on the server.