

### 3RT1075-6AP36

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rt1075-6ap36
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	4.64 kgs
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85364900
Copper Weight	0
EAN	4011209508330.0
Quantity in Package	1
Product Code	3706
UPC	754554772684.0
Product ID	3RT1075-6AP36
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	DE
ECCN	N
eClass 6	27-37-10-03
eClass 7.1	27-37-10-03
eClass 8	27-37-10-03
eClass Version 9	27-37-10-03
eClass Version 9.1	27-37-10-03
ETIM 7	EC000066
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LF0-----
Packaging Length	233,00
Packaging Width	289,00
Packaging Height	272,00
Packaging Size	MM
Product Description	STYCZNIK, 200KW/400V/AC-3 AC/DC ZNAMION. NAP. STERUJĄCE 220-240V UC STYKI POM. 2NO+2NC 3-P, WLK. S12 PRZYŁĄCZE SZYNOWE - NAPĘD KONWENCJ.
Comparative Metals Coefficient	01.05.2012
REACH	Lead CAS-Nr. 7439-92-1
Unit of Measure	ST

## Description

3RT1075-6AP36 | Siemens Contactor, 3 Poles, 400 A | Brand / Manufacturer: Siemens | mass: 9.9 | product type: Contactor | number of bars: 3 | contact configuration: 3NO | current rating: 400 A | power classification: 200 kW | supply voltage: 400 V (Operating);220 to 240 V ac (Control) | size: S12 | type of tension: AC;DC | frequency classification: 50 Hz;60 Hz | number of auxiliary contacts: 2NC;2NO