

### 3RT20161VB41

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rt20161vb41
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Legacy / discontinued

## Technical specification

AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.10.2009
Configurable Product	False
Country of Origin	DE
ECCN	N
eClass 6	27-37-10-03
eClass 7.1	27-37-10-03
eClass 8	27-37-10-03
eClass Version 9	27-37-10-03
eClass Version 9.1	27-37-10-03
ETIM 7	EC000066
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LDP-----
Packaging Length	61,50
Packaging Width	50,00
Packaging Height	77,50
Packaging Size	MM
Product Description	STYCZNIK SPRZĘGAJĄCY, AC-3, 4KW/400V, 1N0, DC 24V, 0.85... 1.85*US, Z DIODĄ, 3-POLOWY, ROZMIAR S00, PRZYŁ. ŚRUBOWE
Comparative Metals Coefficient	01.10.2009
REACH	Lead CAS-Nr. 7439-92-1
Unit of Measure	ST
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85364900
Copper Weight	0
EAN	4011209844032.0
Quantity in Package	1
Product Code	5330
UPC	662643908060.0
Weight	297
Product ID	3RT2016-1VB41

## Description

Power contactor, AC-3 9 A, 4 kW / 400 V 1 NO, 24 V DC 0.85-1.85\* US, with diode integrated, 3-pole, Size S00, screw terminal