

### 3RT2023-1AB00

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rt2023-1ab00
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.45 kgs
<b>Product ID</b>	3RT2023-1AB00
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.10.2009
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>ECCN</b>	N
<b>eClass 6</b>	27-37-10-03
<b>eClass 7.1</b>	27-37-10-03
<b>eClass 8</b>	27-37-10-03
<b>eClass Version 9</b>	27-37-10-03
<b>eClass Version 9.1</b>	27-37-10-03
<b>ETIM 7</b>	EC000066
<b>Aluminium Weight</b>	0
<b>Argent Weight</b>	0
<b>Customs Tariff Code</b>	85364900
<b>Copper Weight</b>	0
<b>EAN</b>	4011209831247.0
<b>Quantity in Package</b>	1
<b>Product Code</b>	5336
<b>UPC</b>	662643912005.0
<b>Group Classification Key</b>	R711
<b>List of Characteristics</b>	CC-IC10
<b>Metals Coefficient</b>	LE0-----
<b>Packaging Length</b>	92,00
<b>Packaging Width</b>	54,00
<b>Packaging Height</b>	105,50
<b>Packaging Size</b>	MM
<b>Product Description</b>	STYCZNIK, AC-3, 4KW/400V, 1N0+1NC, AC 24V 50HZ, 3-POLOWY, ROZMIAR S0, PRZYŁ. ŚRUBOWE
<b>Comparative Metals Coefficient</b>	01.10.2009
<b>Unit of Measure</b>	ST
<b>AL Field</b>	N