

3RT2023-1BB44

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3rt2023-1bb44 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|--|
| Weight | 0.91 kgs |
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85364900 |
| Copper Weight | 0 |
| EAN | 4011209836877.0 |
| Quantity in Package | 1 |
| Product Code | 5336 |
| UPC | 662643912180.0 |
| Product ID | 3RT2023-1BB44 |
| AL Field | N |
| Compliance | Produkt zgodny z RoHS od: 01.10.2009 |
| Configurable Product | False |
| Country of Origin | DE |
| ECCN | N |
| eClass 6 | 27-37-10-03 |
| eClass 7.1 | 27-37-10-03 |
| eClass 8 | 27-37-10-03 |
| eClass Version 9 | 27-37-10-03 |
| eClass Version 9.1 | 27-37-10-03 |
| ETIM 7 | EC000066 |
| Group Classification Key | R711 |
| List of Characteristics | CC-IC10 |
| Metals Coefficient | LDP----- |
| Packaging Length | 92,00 |
| Packaging Width | 54,00 |
| Packaging Height | 159,00 |
| Packaging Size | MM |
| Product Description | STYCZNIK, AC-3, 4KW/400V, 2NO+2NC, DC 24V, 3-POLOWY, ROZMIAR S0, PRZYŁ. ŚRUBOWE ZDEJMOWALNE STYKI POMOCNICZE |
| Comparative Metals Coefficient | 01.10.2009 |
| Unit of Measure | ST |

Description

power contactor, AC-3 9 A, 4 kW / 400 V 2 NO + 2 NC, 24 V DC 3-pole, Size S0 screw terminal Removable auxiliary switch