

### 3RT2028-1AC20

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rt2028-1ac20
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	0.45 kgs
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85364900
Copper Weight	0
EAN	4011209833753.0
Quantity in Package	1
Product Code	5336
UPC	662643917871.0
eClass Version 9.1	27-37-10-03
ETIM 7	EC000066
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LE0-----
Packaging Length	92,00
Packaging Width	54,00
Packaging Height	105,50
Packaging Size	MM
Product Description	STYCZNIK, AC-3, 18.5KW/400V, 1N0+1NC, AC 24V 50/60HZ, 3-POLOWY, ROZMIAR S0, PRZYŁ. ŚRUBOWE
Comparative Metals Coefficient	01.10.2009
Unit of Measure	ST
eClass 8	27-37-10-03
Product ID	3RT2028-1AC20
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.10.2009
Configurable Product	False
Country of Origin	DE
ECCN	N
eClass 6	27-37-10-03
eClass 7.1	27-37-10-03
eClass Version 9	27-37-10-03

## Description

3RT2028-1AC20 | Siemens, Power Contactor, 24 V ac, 48 kW, 50 A, 3 Poles, Size S0 | Brand / Manufacturer: Siemens | product type: Power Contactor | number of bars: 3 | contact configuration: 3P | current rating: 50 A | power classification: 48 kW | supply voltage: 24 V ac | size: S0 | type of tension: AC | frequency classification: 50/60 Hz | number of auxiliary contacts: 2