

### 3RT2036-3NB30

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rt2036-3nb30
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.91 kgs
<b>ETIM 7</b>	EC000066
<b>Group Classification Key</b>	R711
<b>Metals Coefficient</b>	LDP-----
<b>Packaging Width</b>	62,00
<b>Packaging Height</b>	142,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	stycznik mocy, AC-3e/AC-3, 51 A, 22 kW / 400 V, 3-bieg., AC/DC 20-33 V, 50/60 Hz, ze zintegrowanym warystorem, zestyki pomocnicze: 1 NO + 1 NC, obwód główny: przyłącze śrubowe, obwód sterowniczy i pomocniczy: przyłącze sprężynowe, wielkość: S2,
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one lblREACHCasNo8105
<b>eClass 6</b>	27-37-10-03
<b>eClass 7.1</b>	27-37-10-03
<b>eClass 8</b>	27-37-10-03
<b>eClass Version 9</b>	27-37-10-03
<b>eClass Version 9.1</b>	27-37-10-03
<b>List of Characteristics</b>	CC-IC10
<b>Packaging Length</b>	122,50
<b>Comparative Metals Coefficient</b>	01.10.2014
<b>Unit of Measure</b>	ST
<b>Aluminium Weight</b>	0
<b>Argent Weight</b>	0
<b>Customs Tariff Code</b>	85364900
<b>Copper Weight</b>	0
<b>EAN</b>	4011209941588.0
<b>ECCN</b>	N
<b>Quantity in Package</b>	1
<b>Product Code</b>	5338
<b>UPC</b>	887621916961.0
<b>Product ID</b>	3RT2036-3NB30
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.10.2014
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE