

3RT2038-1NP30

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3rt2038-1np30 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|--|
| Weight | 0.91 kgs |
| Packaging Size | MM |
| Product ID | 3RT2038-1NP30 |
| AL Field | N |
| Configurable Product | False |
| ECCN | N |
| eClass 6 | 27-37-10-03 |
| eClass 7.1 | 27-37-10-03 |
| eClass 8 | 27-37-10-03 |
| eClass Version 9 | 27-37-10-03 |
| eClass Version 9.1 | 27-37-10-03 |
| Group Classification Key | R711 |
| Compliance | Produkt zgodny z RoHS od: 01.10.2014 |
| ETIM 7 | EC000066 |
| Comparative Metals Coefficient | 01.10.2014 |
| REACH | Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368 |
| Packaging Height | 142,00 |
| Unit of Measure | ST |
| Product Description | stycznik mocy, AC-3e/AC-3, 80 A, 37 kW / 400 V, 3-bieg., AC/DC 175-280 V, 50/60 Hz, ze zintegrowanym warystorem, zestyki pomocnicze: 1 NO + 1 NC, przyłącze śrubowe, wielkość: S2 |
| Packaging Width | 62,00 |
| Country of Origin | DE |
| List of Characteristics | CC-IC10 |
| Product Code | 5338 |
| UPC | 887621918385.0 |
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85364900 |
| Copper Weight | 0 |
| EAN | 4011209941168.0 |
| Quantity in Package | 1 |
| Metals Coefficient | LDP----- |
| Packaging Length | 122,50 |