

### 3RT2045-3NP30

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 3rt2045-3np30                    |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

## Technical specification

|                                |   |
|--------------------------------|---|
| Quantity in Package            | 1   |
| Product Code                   | 5370  |
| UPC                            | 804766406706.0  |
| Weight                         | 1820  |
| Product ID                     | 3RT2045-3NP30   |
| AL Field                       | N   |
| Aluminium Weight               | 0   |
| Argent Weight                  | 0   |
| Customs Tariff Code            | 85364900  |
| Compliance                     | Produkt zgodny z RoHS od: 01.03.2017  |
| Configurable Product           | False   |
| Copper Weight                  | 0   |
| Country of Origin              | DE  |
| EAN                            | 4047621024950.0   |
| ECCN                           | EAR99   |
| eClass 6                       | 27-37-10-03   |
| eClass 7.1                     | 27-37-10-03   |
| eClass 8                       | 27-37-10-03   |
| eClass Version 9               | 27-37-10-03   |
| eClass Version 9.1             | 27-37-10-03   |
| ETIM 7                         | EC000066  |
| Group Classification Key       | R711  |
| List of Characteristics        | CC-IC10   |
| Metals Coefficient             | LE0-----  |
| Packaging Length               | 161,00  |
| Packaging Width                | 78,00   |
| Packaging Height               | 170,00  |
| Packaging Size                 | MM  |
| Product Description            | stycznik mocy, AC-3e/AC-3, 80 A, 37 kW / 400 V, 3-bieg., AC/DC 175-280 V, 50/60 Hz, ze zintegrowanym warystorem, zestyki pomocnicze: 1 NO + 1 NC, obwód główny: przyłącze śrubowe, obwód sterowniczy i pomocniczy: przyłącze sprężynowe, wielkość: S3 |
| Comparative Metals Coefficient | 01.03.2017  |
| REACH                          | Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one lblREACHCasNo8105  |
| Unit of Measure                | ST  |