

3RT2046-1NB30

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3rt2046-1nb30 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|---|
| Weight | 1.81 kgs |
| Quantity in Package | 1 |
| Product Code | 5370 |
| UPC | 804766406102.0 |
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85364900 |
| Copper Weight | 0 |
| EAN | 4047621018515.0 |
| Product ID | 3RT2046-1NB30 |
| AL Field | N |
| Compliance | Produkt zgodny z RoHS od: 01.03.2017 |
| Configurable Product | False |
| Country of Origin | DE |
| ECCN | EAR99 |
| eClass 6 | 27-37-10-03 |
| eClass 7.1 | 27-37-10-03 |
| eClass 8 | 27-37-10-03 |
| eClass Version 9 | 27-37-10-03 |
| eClass Version 9.1 | 27-37-10-03 |
| ETIM 7 | EC000066 |
| Group Classification Key | R711 |
| List of Characteristics | CC-IC10 |
| Metals Coefficient | LE0----- |
| Packaging Length | 166,00 |
| Packaging Width | 159,00 |
| Packaging Height | 81,00 |
| Packaging Size | MM |
| Product Description | stycznik mocy, AC-3e/AC-3, 95 A, 45 kW / 400 V, 3-bieg., AC/DC 20-33 V, 50/60 Hz, ze zintegrowanym warystorem, zestyki pomocnicze: 1 NO + 1 NC, przyłącze śrubowe, wielkość: S3 |
| Comparative Metals Coefficient | 01.03.2017 |
| REACH | Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368 |
| Unit of Measure | ST |