

### 3RT2046-1NP34

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 3rt2046-1np34                    |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

## Technical specification

|                                |   |
|--------------------------------|---|
| Aluminium Weight               | 0   |
| Argent Weight                  | 0   |
| Customs Tariff Code            | 85364900  |
| Copper Weight                  | 0   |
| EAN                            | 4047621024912.0   |
| Quantity in Package            | 1   |
| Product Code                   | 5370  |
| Weight                         | 1850  |
| Product ID                     | 3RT2046-1NP34   |
| AL Field                       | N   |
| Compliance                     | Produkt zgodny z RoHS od: 01.03.2017  |
| Configurable Product           | False   |
| Country of Origin              | DE  |
| ECCN                           | EAR99   |
| eClass 6                       | 27-37-10-03   |
| eClass 7.1                     | 27-37-10-03   |
| eClass 8                       | 27-37-10-03   |
| eClass Version 9               | 27-37-10-03   |
| eClass Version 9.1             | 27-37-10-03   |
| ETIM 7                         | EC000066  |
| Group Classification Key       | R711  |
| List of Characteristics        | CC-IC10   |
| Metals Coefficient             | LE0-----  |
| Packaging Length               | 210,00  |
| Packaging Width                | 155,00  |
| Packaging Height               | 80,00   |
| Packaging Size                 | MM  |
| Product Description            | stycznik mocy, AC-3e/AC-3, 95 A, 45 kW / 400 V, 3-bieg., AC/DC 175-280 V, 50/60 Hz, ze zintegrowanym warystorem, zestyki pomocnicze: 2 NO + 2 NC, przyłącze śrubowe, wielkość: S3, łącznik pomocniczy odłączany |
| Comparative Metals Coefficient | 01.03.2017  |
| REACH                          | Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one lblREACHCasNo8105  |
| Unit of Measure                | ST  |
| Article Number                 | 3RT20461NP34  |

|                                     |   |
|-------------------------------------|---|
| <b>Product Family</b>               | SIRIUS 3RT contactors, 3-pole, up to 250 kW |
| <b>Catalog ID</b>                   | CC-IC10                                     |
| <b>Packaging Dimensions</b>         | 6.102 x 8.268 x 3.15                        |
| <b>Package Size Unit of Measure</b> | Inch  |
| <b>Quantity Unit</b>                | 1 Piece                                     |
| <b>Voltage Rating</b>               | 400 V, 280 V                                |
| <b>Product Group</b>                | 5370  |
| <b>Net Weight</b>                   | 4.079 lb                                    |
| <b>Packaging Quantity</b>           | 1 pieces                                    |
| <b>Commodity Code</b>               | 85364900                                    |
| <b>Current Rating</b>               | 95 A  |
| <b>Power</b>                        | 45 kW                                       |
| <b>Number of Poles</b>              | 3   |
| <b>Utilization Category</b>         | AC-3  |