

### 3RV1011-0KA10

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rv1011-0ka10
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	0.24 kgs
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85362010
Copper Weight	0
EAN	4011209263512.0
Quantity in Package	1
Packaging Height	84,00
Product Code	3715
UPC	754554408866.0
Product Description	WYŁĄCZNIK, ZAKRES NASTAW TERM. WYZW. PRZECIĄŻ. 0.9...1.25 A BEZZWŁ. WYZW. ZWARC. NAPDPR. 16 A, WIELKOŚĆ S00, DO OCHRONY SILNIKÓW, CLASS 10, PRZYŁĄCZE ŚRUBOWE, STANDARDOWA ZDOLNOŚĆ ŁĄCZENIOWA
List of Characteristics	CC-IC10
Metals Coefficient	LAP-----
Packaging Length	100,00
Packaging Width	49,00
Packaging Size	MM
REACH	Lead CAS-Nr. 7439-92-1
Unit of Measure	ST
Product ID	3RV1011-0KA10
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.01.2013
Configurable Product	False
Country of Origin	DE
ECCN	N
eClass 6	27-37-04-01
eClass 7.1	27-37-04-01
eClass 8	27-37-04-01
eClass Version 9	27-37-04-01
eClass Version 9.1	27-37-04-01
ETIM 7	EC000074
Group Classification Key	R711
Comparative Metals Coefficient	01.01.2013

## Description

3RV1011-0KA10 | Siemens, Circuit Breaker, 3 Pole, 1.25 A @ 400 V ac 690 V ac, 100000 A, Thermal-Magnetic, 90 x 45 x 81 mm | Brand / Manufacturer: Siemens | height: 45 | width: 90 | depth: 81 | product type: Circuit Breaker | number of bars: 3 | current rating: 1.25 A @ 400 V ac | rated voltage: 690 V ac | type of attachment: DIN Rail Mount | power off: 100000 A @ 240 V ac; 100000 A @ 400 V ac; 100000 A @ 500 V ac; 2000 A @ 690 V ac | type of output terminal: Screw | protection functions: Phase Failure Detection; Short-Circuit | release: Thermal-Magnetic | reset actuator type: Rocker Switch | tripping characteristic: Class 10 | operating temperature range: -20 to +60 °C (Ambient) | Size: 90 x 45 x 81 mm