

### 3RV1011-1CA10

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rv1011-1ca10
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	0.28 kgs
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85362010
Copper Weight	0
EAN	4011209263543.0
Quantity in Package	1
Packaging Height	84,00
Product Code	3715
UPC	754554408927.0
eClass Version 9	27-37-04-01
eClass Version 9.1	27-37-04-01
ETIM 7	EC000074
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LAP-----
Packaging Length	100,00
Packaging Width	49,00
Packaging Size	MM
Product Description	WYŁĄCZNIK, ZAKRES NASTAW TERM. WYZW. PRZECIĄŻ. 1.8...2.5 A, BEZZWŁ. WYZW. ZWARC. NAPDPR. 33 A, WIELKOŚĆ S00, DO OCHRONY SILNIKÓW, CLASS 10, PRZYŁĄCZE ŚRUBOWE, STANDARDOWA ZDOLNOŚĆ ŁĄCZENIOWA
Comparative Metals Coefficient	01.01.2013
REACH	Lead CAS-Nr. 7439-92-1
Unit of Measure	ST
Product ID	3RV1011-1CA10
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.01.2013
Configurable Product	False
Country of Origin	DE
ECCN	N
eClass 6	27-37-04-01
eClass 7.1	27-37-04-01
eClass 8	27-37-04-01

## Description

3RV1011-1CA10 | Siemens, Circuit Breaker, 3 Pole, 2.5 A @ 400 V ac 690 V ac, 100000 A, Thermal-Magnetic, 90 x 45 x 81 mm | Brand / Manufacturer: Siemens | product type: Circuit Breaker | number of bars: 3 | current rating: 2.5 A @ 400 V ac | rated voltage: 690 V ac | type of attachment: DIN Rail Mount | power off: 100000 A @ 240 V ac; 100000 A @ 400 V ac; 10000 A @ 500 V ac; 2000 A @ 690 V ac | type of output terminal: Screw | protection functions: Phase Failure Detection; Short-Circuit | release: Thermal-Magnetic | reset actuator type: Rocker Switch | tripping characteristic: Class 10 | operating temperature range: -20 to +60 °C (Ambient) | Size: 90 x 45 x 81 mm