

### 3RV2411-4AA10-0BA0

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 3rv2411-4aa10-0ba0               |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

## Technical specification

|                                |   |
|--------------------------------|---|
| Product ID                     | 3RV2411-4AA10-0BA0  |
| AL Field                       | N   |
| Aluminium Weight               | 0   |
| Argent Weight                  | 0   |
| Customs Tariff Code            | 85362090  |
| Compliance                     | Produkt zgodny z RoHS od: 01.10.2009  |
| Configurable Product           | False   |
| Copper Weight                  | 0   |
| Country of Origin              | DE  |
| EAN                            | 4011209936065.0   |
| ECCN                           | N   |
| eClass 6                       | 27-37-04-09   |
| eClass 7.1                     | 27-37-04-09   |
| eClass 8                       | 27-37-04-09   |
| eClass Version 9               | 27-37-04-09   |
| eClass Version 9.1             | 27-37-04-09   |
| ETIM 7                         | EC000228  |
| Group Classification Key       | R711  |
| List of Characteristics        | CC-IC10   |
| Metals Coefficient             | LAP-----  |
| Quantity in Package            | 1   |
| Packaging Length               | 102,00  |
| Packaging Width                | 49,00   |
| Packaging Height               | 102,00  |
| Packaging Size                 | MM  |
| Product Description            | typ specjalny wyłącznik wielkość 500 do ochrony transformatora wyzwalacz A 10...16 A wyzwalacz N 286 A przyłącze śrubowe standardowa zdolność załączania temperatura otoczenia -50 °C 500 cykli przestawieniowych |
| Product Code                   | 5332  |
| Comparative Metals Coefficient | 01.10.2009  |
| REACH                          | Lead CAS-Nr. 7439-92-1  |
| Unit of Measure                | ST  |
| UPC                            | 195125089617.0  |
| Weight                         | 355   |
| Article Number                 | 3RV24114AA100BA0  |

|                                     |                        |
|-------------------------------------|------------------------|
| <b>Product Family</b>               | Ordering Data Overview |
| <b>Catalog ID</b>                   | CC-IC10                |
| <b>Packaging Dimensions</b>         | 1.929 x 4.016 x 4.016  |
| <b>Package Size Unit of Measure</b> | Inch                   |
| <b>Quantity Unit</b>                | 1 Piece                |
| <b>Current Rating</b>               | 16, 286 A              |
| <b>Product Group</b>                | 5332                   |
| <b>Net Weight</b>                   | 0.783 lb               |
| <b>Packaging Quantity</b>           | 1 pieces               |
| <b>Commodity Code</b>               | 85362090               |
| <b>Operating Temperature</b>        | 0 °C                   |
| <b>Trip Curve</b>                   | C                      |