

3RW3017-1BB04

Industrial automation components

Manufacturer	Siemens
Catalog number	3rw3017-1bb04
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.09 kgs
Product ID	3RW3017-1BB04
Compliance	Produkt zgodny z RoHS od: 01.07.2006
Configurable Product	False
Country of Origin	CZ
ECCN	N
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07
eClass 8	27-37-09-07
eClass Version 9	27-37-09-07
eClass Version 9.1	27-37-09-07
ETIM 7	EC000640
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LB0-----
Packaging Width	126,00
Packaging Height	60,00
Packaging Size	MM
Product Description	SIRIUS SOFTSTART, WLK. S00, 12.5A, 5.5KW/400V, 40 ST., 200-480V AC, 24V AC/DC, ZACISKI ŚRUBOWE,
Comparative Metals Coefficient	01.07.2006
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Lead titanium zirconium oxide lblREACHCasNo0830
Unit of Measure	ST
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
EAN	4011209719637.0
Quantity in Package	1
Product Code	5345
UPC	40892691887.0
AL Field	N
Packaging Length	164,00

Description

3RW3017-1BB04 | Siemens, Soft Starter, Soft Starter, 5.5 kW, 200 to 460 V ac, 12.5 A, '3 Phase, 50 Hz, 60 Hz, Snap On Mount, Screw Terminal | Brand / Manufacturer: Siemens | product type: Soft Starter | type of motor starter: Soft Starter | power classification: 5.5 kW | control voltage: 200 to 460 V ac | current rating: 12.5 A | phase: 3 | minimum operating frequency: 50 Hz | maximum operating frequency: 60 Hz | type of attachment: Snap On Mount | voltage on terminals: Screw | minimum operating temperature: -25 °C | maximum working temperature: +60 °C | Total length: 45 mm | total width: 150 mm | overall depth: 125 mm