

### 3RW3017-2BB04

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rw3017-2bb04
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Product ID	3RW3017-2BB04
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.07.2006
Configurable Product	False
Country of Origin	CZ
ECCN	N
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07
eClass 8	27-37-09-07
eClass Version 9	27-37-09-07
eClass Version 9.1	27-37-09-07
ETIM 7	EC000640
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LB0-----
Packaging Length	126,00
Packaging Width	210,00
Packaging Height	165,00
Packaging Size	MM
Product Description	SIRIUS SOFTSTART, WLK. S00, 12.5A, 5.5KW/400V, 40 ST., 200-480V AC, 24V AC/DC, ZACISKI SPRĘŻYNOWE,
Comparative Metals Coefficient	01.07.2006
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Lead titanium zirconium oxide lblREACHCasNo0830
Unit of Measure	ST
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
EAN	4011209719729.0
Quantity in Package	1
Product Code	5345
UPC	754554958200.0
Weight	464

## Description

3RW3017-2BB04 | Siemens, Soft Starter, 5.5 kW, 12.5, 3 Phase, 45 x 150 x 120 mm | Brand / Manufacturer: Siemens | product type: Soft Starter | type of motor starter: SIRIUS Soft Starter | power classification: 5.5 kW | control voltage: 400 V;200 to 480 V ac;24 V ac/dc | current rating: 12.5 A | phase: 3 | minimum operating frequency: 50 Hz | maximum operating frequency: 60 Hz | type of attachment: Screw Mount;Snap On Mount | voltage on terminals: Spring