

### 3RW30362BB14

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rw30362bb14
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Legacy / discontinued

## Technical specification

Product ID	3RW3036-2BB14
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	CZ
Product Description	SIRIUS SOFTSTART, WLK. S2, 45A, 22KW/400V, 40 ST., 200-480V AC, 110-230V AC/DC, ZACISKI SPREŻYNOWE,
Comparative Metals Coefficient	01.05.2012
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Lead titanium zirconium oxide lblREACHCasNo0830
Unit of Measure	ST
EAN	4011209719330.0
ECCN	N
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07
eClass 8	27-37-09-07
eClass Version 9	27-37-09-07
ETIM 7	EC000640
Group Classification Key	R711
Metals Coefficient	LB0-----
Quantity in Package	1
List of Characteristics	CC-IC10
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
Product Code	5345
UPC	754554958514.0
Weight	1159
eClass Version 9.1	27-37-09-07
Packaging Length	170,00
Packaging Width	70,00
Packaging Height	198,00
Packaging Size	MM

## Description

SIRIUS soft starter S2 45 A, 22 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC spring-type terminals