

3RW30462BB14

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3rw30462bb14 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|---|
| eClass 6 | 27-37-09-07 |
| eClass 7.1 | 27-37-09-07 |
| eClass 8 | 27-37-09-07 |
| eClass Version 9 | 27-37-09-07 |
| eClass Version 9.1 | 27-37-09-07 |
| Quantity in Package | 1 |
| Packaging Length | 219,00 |
| Packaging Width | 222,00 |
| Packaging Height | 86,00 |
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85371098 |
| Copper Weight | 0 |
| EAN | 4011209719231.0 |
| ECCN | N |
| ETIM 7 | EC000640 |
| Group Classification Key | R711 |
| List of Characteristics | CC-IC10 |
| Metals Coefficient | LB0----- |
| Packaging Size | MM |
| Product ID | 3RW3046-2BB14 |
| AL Field | N |
| Compliance | Produkt zgodny z RoHS od: 01.05.2012 |
| Configurable Product | False |
| Country of Origin | CZ |
| Product Description | SIRIUS SOFTSTART, WLK. S3, 80A, 45KW/400V, 40 ST., 200-480V AC, 110-230V AC/DC, ZACISKI SPRĘŻYNOWE, |
| REACH | Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) \b\lREACHCasNo7368; Lead titanium zirconium oxide \b\lREACHCasNo0830 |
| Unit of Measure | ST |
| Product Code | 5345 |
| Comparative Metals Coefficient | 01.05.2012 |
| UPC | 754554958545.0 |
| Weight | 1696 kg |

Description

SIRIUS soft starter S3 80 A, 45 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC spring-type terminals