

### 3RW40262TB04

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rw40262tb04
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	750 kg
<b>Aluminium Weight</b>	0
<b>Argent Weight</b>	0
<b>Customs Tariff Code</b>	85371098
<b>Copper Weight</b>	0
<b>eClass 6</b>	27-37-09-07
<b>eClass 7.1</b>	27-37-09-07
<b>eClass 8</b>	27-37-09-07
<b>eClass Version 9</b>	27-37-09-07
<b>eClass Version 9.1</b>	27-37-09-07
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	155,00
<b>Packaging Width</b>	60,00
<b>Packaging Height</b>	182,00
<b>Product Code</b>	3727
<b>Comparative Metals Coefficient</b>	01.07.2006
<b>UPC</b>	195125182141.0
<b>Product ID</b>	3RW4026-2TB04
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.07.2006
<b>Configurable Product</b>	False
<b>Country of Origin</b>	Germany
<b>ECCN</b>	EAR99
<b>ETIM 7</b>	EC000640
<b>Group Classification Key</b>	R711
<b>List of Characteristics</b>	CC-IC10
<b>Metals Coefficient</b>	LA0-----
<b>Packaging Size</b>	MM
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one lblREACHCasNo8105; Lead titanium zirconium oxide lblREACHCasNo0830
<b>Unit of Measure</b>	ST
<b>Product Description</b>	SIRIUS soft starter S0 25 A, 11 kW/400 V, 40 °C 200-480 V AC, 24 V AC/DC spring-type terminals Thermistor motor protection
<b>EAN</b>	4011209694118

<b>Product Family</b>	3RW40 soft starters
<b>Packaging Dimensions</b>	2.264 x 6.142 x 7.126
<b>Package Size Unit of Measure</b>	Inch
<b>Quantity Unit</b>	1 Piece
<b>Voltage Rating</b>	400 V, 480 V, 24 V
<b>Article Number</b>	3RW40262TB04
<b>Product Group</b>	3727
<b>Net Weight</b>	1.631 lb
<b>Packaging Quantity</b>	1 pieces
<b>Catalog ID</b>	CC-IC10
<b>Commodity Code</b>	85371098
<b>Current Rating</b>	25 A
<b>Power</b>	11 kW

## Description

SIRIUS SOFTSTART, S0, 25A, 11KW/400V, 40 PCS., AC 200-480V, AC/DC 24V, with spring terminals and thermistor motor protection, weight 0.91 kg.