

### 3RW4027-1BB14

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rw4027-1bb14
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	0.45 kgs
Product ID	3RW4027-1BB14
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.07.2006
Configurable Product	False
Country of Origin	CZ
ECCN	EAR99
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07
eClass 8	27-37-09-07
eClass Version 9	27-37-09-07
eClass Version 9.1	27-37-09-07
ETIM 7	EC000640
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Packaging Length	181,00
Packaging Width	155,00
Packaging Height	58,00
Packaging Size	MM
Product Description	SIRIUS SOFTSTART, WLK. S0, 32A, 15KW/400V, 40 ST., AC 200-480V, AC/DC 110-230V, ZACISKI ŚRUBOWE,
Comparative Metals Coefficient	01.07.2006
Unit of Measure	ST
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one lblREACHCasNo8105; Lead titanium zirconium oxide lblREACHCasNo0830
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
EAN	4011209691728.0
Quantity in Package	1
Product Code	3727

## Description

3RW4027-1BB14 | Siemens, Soft Starter, Soft Starter, 15 kW, 200 to 480 V ac, 32 A, '3 Phase, 50 Hz, 60 Hz, Snap On Mount, Screw Terminal | Brand / Manufacturer: Siemens | product type: Soft Starter | type of motor starter: Soft Starter | power classification: 15 kW | control voltage: 200 to 480 V ac | current rating: 32 A | phase: 3 | minimum operating frequency: 50 Hz | maximum operating frequency: 60 Hz | type of attachment: Snap On Mount | voltage on terminals: Screw | minimum operating temperature: -25 °C | maximum working temperature: +60 °C | Total length: 45 mm | total width: 155 mm | overall depth: 125 mm