

3RW40272TB05

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3rw40272tb05 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Legacy / discontinued |

Technical specification

| | |
|--------------------------------|---|
| Packaging Length | 183,00 |
| Product ID | 3RW4027-2TB05 |
| Compliance | Produkt zgodny z RoHS od: 01.07.2006 |
| Configurable Product | False |
| Country of Origin | CZ |
| Product Description | SIRIUS SOFTSTART, WLK. S0, 32A, 18.5KW/500V, 40 ST., AC 400-600V, AC/DC 24V, ZACISKI SPRĘŻYNOWE, Z TERMISTOROWĄ OCHR. SILNIKÓW, |
| Comparative Metals Coefficient | 01.07.2006 |
| ECCN | EAR99 |
| eClass 6 | 27-37-09-07 |
| eClass 7.1 | 27-37-09-07 |
| eClass 8 | 27-37-09-07 |
| eClass Version 9 | 27-37-09-07 |
| eClass Version 9.1 | 27-37-09-07 |
| Quantity in Package | 1 |
| Packaging Size | MM |
| Product Code | 3727 |
| REACH | Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one lblREACHCasNo8105; Lead titanium zirconium oxide lblREACHCasNo0830 |
| UPC | 804766960710.0 |
| Weight | 775 |
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85371098 |
| Copper Weight | 0 |
| EAN | 4011209695351.0 |
| AL Field | N |
| Unit of Measure | ST |
| ETIM 7 | EC000640 |
| Group Classification Key | R711 |
| List of Characteristics | CC-IC10 |
| Metals Coefficient | LA0----- |
| Packaging Width | 210,00 |
| Packaging Height | 58,00 |

| | |
|-------------------------------------|-----------------------|
| Article Number | 3RW40272TB05 |
| Product Family | 3RW40 soft starters |
| Product Group | 3727 |
| Catalog ID | CC-IC10 |
| Net Weight | 1.676 lb |
| Packaging Dimensions | 2.264 x 6.142 x 7.126 |
| Package Size Unit of Measure | Inch |
| Quantity Unit | 1 Piece |
| Packaging Quantity | 1 pieces |
| Commodity Code | 85371098 |
| Current Rating | 32 A |
| Voltage Rating | 500 V, 600 V, 24 V |

Description

SIRIUS soft starter S0 32 A, 18.5 k kW/500 V, 40 °C 400-600 V AC, 24 V AC/DC spring-type terminals Thermistor motor protection