

3RW4028-1BB14

Industrial automation components

Manufacturer	Siemens
Catalog number	3rw4028-1bb14
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.09 kgs
Product ID	3RW4028-1BB14
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.07.2006
Configurable Product	False
Country of Origin	CZ
ECCN	EAR99
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07
eClass 8	27-37-09-07
eClass Version 9	27-37-09-07
eClass Version 9.1	27-37-09-07
ETIM 7	EC000640
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Packaging Length	180,00
Packaging Width	154,00
Packaging Height	58,00
Packaging Size	MM
Comparative Metals Coefficient	01.07.2006
Unit of Measure	ST
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
EAN	4011209691780.0
Quantity in Package	1
Product Code	3727
Product Description	SIRIUS SOFTSTART, WLK. S0, 38A, 18.5KW/400V, 40 ST., AC 200-480V, AC/DC 110-230V, ZACISKI ŚRUBOWE,
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) \b\REACHCasNo7368; 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one \b\REACHCasNo8105; Lead titanium zirconium oxide \b\REACHCasNo0830

Description

3RW4028-1BB14 | Siemens, Soft Starter, 110 to 230 V ac/dc, 38 A | Brand / Manufacturer: Siemens | product type: Soft Starter | type of motor starter: SIRIUS Soft Starter | power classification: 18.5 W @ 400 V | control voltage: 110 to 230 V ac/dc | current rating: 38 A | phase: 3 | minimum operating frequency: 50 Hz | maximum operating frequency: 60 Hz | type of attachment: Screw Mount;Snap On Mount | voltage on terminals: Screw | minimum operating temperature: -25 °C | maximum working temperature: +60 °C | Total length: 125 mm | total width: 45 mm | overall depth: 154 mm