

### 3RW4036-1BB04

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rw4036-1bb04
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	0.60 kgs
Product ID	3RW4036-1BB04
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	CZ
ECCN	EAR99
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07
eClass 8	27-37-09-07
eClass Version 9	27-37-09-07
eClass Version 9.1	27-37-09-07
ETIM 7	EC000640
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Packaging Length	197,00
Packaging Width	167,00
Packaging Height	71,00
Packaging Size	MM
Product Description	SIRIUS SOFTSTART, WLK. S2, 45A, 22KW/400V, 40 ST., AC 200-480V, AC/DC 24V, ZACISKI ŚRUBOWE,
Comparative Metals Coefficient	01.05.2012
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) \b1REACHCasNo7368; Lead titanium zirconium oxide \b1REACHCasNo0830; Perfluorobutane sulfonic acid (PFBS) and its salts \b1REACHCasNo0211
Unit of Measure	ST
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
EAN	4011209691827.0
Quantity in Package	1
Product Code	3727
UPC	754554958606.0

## Description

3RW4036-1BB04 | Siemens, Soft Starter, 200 to 480 V ac, 3 Phase | Brand / Manufacturer: Siemens | height: 169 | width: 685 | depth: 195 | mass: 1.3 | product type: Soft Starter | type of motor starter: SIRIUS Soft Starter | power classification: 22 kW | control voltage: 200 to 480 V ac;24 V ac/dc;400 V | current rating: 45 A | phase: 3 | minimum operating frequency: 50 Hz | maximum operating frequency: 60 Hz | type of attachment: DIN Rail Mount | voltage on terminals: Screw | minimum operating temperature: -25 °C | maximum working temperature: 60 °C | Total length: 55 mm | total width: 170 mm | overall depth: 160 mm