

3RW4036-1TB04

Industrial automation components

Manufacturer	Siemens
Catalog number	3rw4036-1tb04
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	1.36 kgs
Product ID	3RW4036-1TB04
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	CZ
ECCN	EAR99
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07
eClass 8	27-37-09-07
eClass Version 9	27-37-09-07
eClass Version 9.1	27-37-09-07
ETIM 7	EC000640
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Packaging Length	70,00
Packaging Width	197,00
Packaging Height	170,00
Packaging Size	MM
Product Description	SIRIUS SOFTSTART, WLK. S2, 45A, 22KW/400V, 40 ST., AC 200-480V, AC/DC 24V, ZACISKI ŚRUBOWE, Z TERMISTOROWĄ OCHR. SILNIKÓW,
Comparative Metals Coefficient	01.05.2012
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Lead titanium zirconium oxide lblREACHCasNo0830; Perfluorobutane sulfonic acid (PFBS) and its salts lblREACHCasNo0211
Unit of Measure	ST
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
EAN	4011209691834.0
Quantity in Package	1
Product Code	3727
UPC	40892653595.0

Description

3RW4036-1TB04 | Siemens, Soft Starter, 24 V ac/dc, 45 A | Brand / Manufacturer: Siemens | height: 169 | width: 68 | depth: 195 | mass: 1.3 | product type: Soft Starter | type of motor starter: SIRIUS Soft Starter | power classification: 22 W @ 400 V | control voltage: 24 V ac/dc | current rating: 45 A | phase: 3 | minimum operating frequency: 50 Hz | maximum operating frequency: 60 Hz | type of attachment: Screw Mount;Snap On Mount | voltage on terminals: Screw | minimum operating temperature: -25 °C | maximum working temperature: +60 °C | Total length: 144 mm | total width: 55 mm | overall depth: 170 mm