

### 3RW40362BB15

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rw40362bb15
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

ECCN	EAR99
ETIM 7	EC000640
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Packaging Size	MM
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
EAN	4011209696334.0
Product Code	3727
Comparative Metals Coefficient	01.05.2012
UPC	754554959023.0
Weight	1262 kg
Product ID	3RW4036-2BB15
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	CZ
Product Description	SIRIUS SOFTSTART, WLK. S2, 45A, 30KW/500V, 40 ST., AC 400-600V, AC/DC 110-230V, ZACISKI SPRĘŻYNOWE,
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Lead titanium zirconium oxide lblREACHCasNo0830
Unit of Measure	ST
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07
eClass 8	27-37-09-07
eClass Version 9	27-37-09-07
eClass Version 9.1	27-37-09-07
Quantity in Package	1
Packaging Length	197,00
Packaging Width	169,00
Packaging Height	71,00

## Description

SIRIUS soft starter S2 45 A, 30 kW/500 V, 40 °C 400-600 V AC, 110-230 V AC/DC spring-type terminals