

### 3RW40382BB14

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rw40382bb14
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
EAN	4011209696440.0
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07
eClass 8	27-37-09-07
eClass Version 9	27-37-09-07
eClass Version 9.1	27-37-09-07
Quantity in Package	1
Packaging Length	169,00
Packaging Width	70,00
Packaging Height	198,00
Product Code	3727
Comparative Metals Coefficient	01.05.2012
UPC	754554953014.0
Product ID	3RW4038-2BB14
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	CZ
ECCN	N
ETIM 7	EC000640
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Packaging Size	MM
Product Description	SIRIUS SOFTSTART, WLK. S2, 72A, 37KW/400V, 40 ST., AC 200-480V, AC/DC 110-230V, ZACISKI SPRĘŻYNOWE,
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Lead titanium zirconium oxide lblREACHCasNo0830
Unit of Measure	ST
Weight	1284 kg

## Description

SIRIUS SOFTSTART, WLK. S2, 72A, 37KW/400V, 40 ST., AC 200-480V, AC/DC 110-230V, SPRING TERMINALS. The product is RoHS compliant since 01.05.2012 and is manufactured in the Czech Republic. It weighs 0.62 kg, with packaging dimensions of 169 mm in length, 70 mm in width, and 198 mm in height. The product is not configurable and is supplied in a single unit package. Compliance with eClass 6, 7.1, 8, and 9.1: 27-37-09-07.