

### 3RW40382BB15

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rw40382bb15
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

ECCN	N
ETIM 7	EC000640
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Packaging Size	MM
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
Product ID	3RW4038-2BB15
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	CZ
Product Description	SIRIUS SOFTSTART, WLK. S2, 72A, 45KW/500V, 40 ST., AC 400-600V, AC/DC 110-230V, ZACISKI SPRĘŻYNOWE,
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Lead titanium zirconium oxide lblREACHCasNo0830
Unit of Measure	ST
Product Code	3727
Comparative Metals Coefficient	01.05.2012
UPC	754554959047.0
Weight	1268 kg
EAN	4011209696471.0
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07
eClass 8	27-37-09-07
eClass Version 9	27-37-09-07
eClass Version 9.1	27-37-09-07
Quantity in Package	1
Packaging Length	196,00
Packaging Width	167,00
Packaging Height	71,00

## Description

SIRIUS SOFTSTART, WLK. S2, 72A, 45KW/500V, 40 ST., AC 400-600V, AC/DC 110-230V, SPRING TERMINALS. RoHS compliant since 01.05.2012, manufactured in the Czech Republic. Weight: 1268 g, packaging dimensions: 196x167x71 mm.