

3RW4046-1BB14

Industrial automation components

Manufacturer	Siemens
Catalog number	3rw4046-1bb14
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.04 kgs
Product ID	3RW4046-1BB14
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	CZ
ECCN	N
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07
eClass 8	27-37-09-07
eClass Version 9	27-37-09-07
eClass Version 9.1	27-37-09-07
ETIM 7	EC000640
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Packaging Length	183,00
Packaging Width	88,00
Packaging Height	220,00
Packaging Size	MM
Product Description	SIRIUS SOFTSTART, WLK. S3, 80A, 45KW/400V, 40 ST., AC 200-480V, AC/DC 110-230V, ZACISKI ŚRUBOWE,
Comparative Metals Coefficient	01.05.2012
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) \b1REACHCasNo7368; Lead titanium zirconium oxide \b1REACHCasNo0830
Unit of Measure	ST
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
EAN	4011209693258.0
Quantity in Package	1
Product Code	3727

Description

3RW4-046-1BB14 | Siemens, Soft Starter, 110 to 230 V ac/dc, 80 A | Brand / Manufacturer: Siemens | product type: Soft Starter | type of motor starter: SIRIUS Soft Starter | power classification: 45 W @ 400 V | control voltage: 110 to 230 V ac/dc | current rating: 80 A | phase: 3 | minimum operating frequency: 50 Hz | maximum operating frequency: 60 Hz | type of attachment: Screw Mount;Snap On Mount | voltage on terminals: Screw | minimum operating temperature: -25 °C | maximum working temperature: +60 °C | Total length: 160 mm | total width: 70 mm | overall depth: 188 mm