

3RW40461BB05

Industrial automation components

Manufacturer	Siemens
Catalog number	3rw40461bb05
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

ECCN	N
eClass 8	27-37-09-07
ETIM 7	EC000640
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Quantity in Package	1
Packaging Length	220,00
Packaging Width	220,00
Packaging Height	91,00
Packaging Size	MM
Product Description	SIRIUS SOFTSTART, WLK. S3, 80A, 55KW/500V, 40 ST., AC 400-600V, AC/DC 24V, ZACISKI ŚRUBOWE,
Product Code	3727
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
Product ID	3RW4046-1BB05
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	CZ
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) \b\REACHCasNo7368; Lead titanium zirconium oxide \b\REACHCasNo0830; Perfluorobutane sulfonic acid (PFBS) and its salts \b\REACHCasNo0211
Unit of Measure	ST
UPC	754554958804.0
Weight	1874 kg
EAN	4011209693289.0
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07
eClass Version 9	27-37-09-07
eClass Version 9.1	27-37-09-07
Comparative Metals Coefficient	01.05.2012

Description

The SIRIUS SOFTSTART is an advanced motor starting device designed for applications operating at AC 400-600V and AC/DC 24V. It provides performance up to 80A and a power rating of 55KW at 500V. The product features screw terminals and complies with RoHS and REACH regulations. Packaging dimensions are 220x220x91 mm, with a weight of 1874 g. Compliance with eClass 8: 27-37-09-07 and ETIM 7: EC000640 confirms its high quality and industrial applicability.