

3RW40461BB15

Industrial automation components

Manufacturer	Siemens
Catalog number	3rw40461bb15
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Packaging Size	MM
eClass Version 9	27-37-09-07
eClass Version 9.1	27-37-09-07
ETIM 7	EC000640
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Packaging Width	88,00
Weight	1849 kg
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
EAN	4011209693296.0
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07
eClass 8	27-37-09-07
Product Code	3727
Comparative Metals Coefficient	01.05.2012
UPC	754554958873.0
Product ID	3RW4046-1BB15
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	CZ
ECCN	N
Product Description	SIRIUS SOFTSTART, WLK. S3, 80A, 55KW/500V, 40 ST., AC 400-600V, AC/DC 110-230V, ZACISKI ŚRUBOWE,
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Lead titanium zirconium oxide lblREACHCasNo0830
Unit of Measure	ST
Quantity in Package	1
Packaging Length	183,00
Packaging Height	220,00

Description

The SIRIUS SOFTSTART is an advanced motor starting device designed for applications operating at AC voltages of 400-600V and AC/DC voltages of 110-230V. It offers a maximum current of 80A and a power rating of 55kW at 500V. The product features a robust design with screw terminals for easy installation. Compliant with RoHS and REACH regulations, this product is manufactured in the Czech Republic. Packaging dimensions are 183 mm in length, 88 mm in width, and 220 mm in height, with a weight of 1.36 kg.