

### 3RW40462BB05

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rw40462bb05
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

ECCN	N
ETIM 7	EC000640
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Quantity in Package	1
Packaging Size	MM
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
Aluminium Weight	0
Product ID	3RW4046-2BB05
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	CZ
Product Description	SIRIUS SOFTSTART, WLK. S3, 80A, 55KW/500V, 40 ST., AC 400-600V, AC/DC 24V, ZACISKI SPRĘŻYNOWE,
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Lead titanium zirconium oxide lblREACHCasNo0830; Perfluorobutane sulfonic acid (PFBS) and its salts lblREACHCasNo0211
Unit of Measure	ST
Product Code	3727
Comparative Metals Coefficient	01.05.2012
UPC	754554958965.0
Weight	1849 kg
EAN	4011209696518.0
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07
eClass 8	27-37-09-07
eClass Version 9	27-37-09-07
eClass Version 9.1	27-37-09-07
Packaging Length	183,00
Packaging Width	90,00
Packaging Height	220,00

## Description

SIRIUS SOFTSTART, S3, 80A, 55KW/500V, 40 ST., AC 400-600V, AC/DC 24V, SPRING TERMINALS.  
RoHS compliant since 01.05.2012, country of origin CZ. Weight: 1849 g, packaging dimensions: 183x90x220 mm.