

### 3RW40462TB05

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rw40462tb05
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>ECCN</b>	N
<b>ETIM 7</b>	EC000640
<b>Group Classification Key</b>	R711
<b>List of Characteristics</b>	CC-IC10
<b>Metals Coefficient</b>	LA0-----
<b>Quantity in Package</b>	1
<b>Packaging Width</b>	184,00
<b>Packaging Height</b>	86,00
<b>Packaging Size</b>	MM
<b>Customs Tariff Code</b>	85371098
<b>EAN</b>	4011209696532.0
<b>Product Code</b>	3727
<b>Comparative Metals Coefficient</b>	01.05.2012
<b>UPC</b>	804766281662.0
<b>Weight</b>	1844 kg
<b>Aluminium Weight</b>	0
<b>Argent Weight</b>	0
<b>Copper Weight</b>	0
<b>Product ID</b>	3RW4046-2TB05
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.05.2012
<b>Configurable Product</b>	False
<b>Country of Origin</b>	CZ
<b>Product Description</b>	SIRIUS SOFTSTART, WLK. S3, 80A, 55KW/500V, 40 ST., AC 400-600V, AC/DC 24V, ZACISKI SPRĘŻYNOWE, Z TERMISTOROWĄ OCHR. SILNIKÓW,
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Lead titanium zirconium oxide lblREACHCasNo0830; Perfluorobutane sulfonic acid (PFBS) and its salts lblREACHCasNo0211
<b>Unit of Measure</b>	ST
<b>eClass 6</b>	27-37-09-07
<b>eClass 7.1</b>	27-37-09-07
<b>eClass 8</b>	27-37-09-07
<b>eClass Version 9</b>	27-37-09-07
<b>eClass Version 9.1</b>	27-37-09-07
<b>Packaging Length</b>	218,00

## Description

SIRIUS soft starter S3 80 A, 55 kW/500 V, 40 °C 400-600 V AC, 24 V AC/DC spring-type terminals Thermistor motor protection