

3RW4047-1TB04

Industrial automation components

Manufacturer	Siemens
Catalog number	3rw4047-1tb04
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.82 kgs
Product ID	3RW4047-1TB04
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	CZ
ECCN	N
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07
eClass 8	27-37-09-07
eClass Version 9	27-37-09-07
eClass Version 9.1	27-37-09-07
ETIM 7	EC000640
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Packaging Length	219,00
Packaging Width	182,00
Packaging Height	88,00
Packaging Size	MM
Comparative Metals Coefficient	01.05.2012
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Lead titanium zirconium oxide lblREACHCasNo0830; Perfluorobutane sulfonic acid (PFBS) and its salts lblREACHCasNo0211
Unit of Measure	ST
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
EAN	4011209693319.0
Quantity in Package	1
Product Code	3727
UPC	40892655339.0
AL Field	N
Product Description	SIRIUS SOFTSTART, WLK. S3, 106A, 55KW/400V, 40 ST., AC 200-480V, AC/DC 24V, ZACISKI ŚRUBOWE, Z TERMISTOROWĄ OCHR. SILNIKÓW,

Description

3RW4047-1TB04 | Siemens, Soft Starter, 55 kW @ 400 V, 200 to 480 V ac, 106 A, 3 Phase, Screw Terminal, 170 x 70 x 190 mm | Brand / Manufacturer: Siemens | height: 182 | width: 86 | depth: 216 | mass: 1.88 | product type: Soft Starter | type of motor starter: Soft Starter | power classification: 55 kW @ 400 V | control voltage: 200 to 480 V ac | current rating: 106 A | phase: 3 | minimum operating frequency: 50 Hz | maximum operating frequency: 60 Hz | type of attachment: Snap-On Mount | voltage on terminals: Screw