

### 3RW4047-2BB14

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rw4047-2bb14
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Legacy / discontinued

## Technical specification

Weight	0.37 kgs
Product ID	3RW4047-2BB14
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	CZ
ECCN	N
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07
eClass 8	27-37-09-07
eClass Version 9	27-37-09-07
eClass Version 9.1	27-37-09-07
ETIM 7	EC000640
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Packaging Length	181,00
Packaging Width	85,00
Packaging Height	220,00
Packaging Size	MM
Product Description	SIRIUS SOFTSTART, WLK. S3, 106A, 55KW/400V, 40 ST., AC 200-480V, AC/DC 110-230V, ZACISKI SPRĘŻYNOWE,
Comparative Metals Coefficient	01.05.2012
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) \b\bREACHCasNo7368; Lead titanium zirconium oxide \b\bREACHCasNo0830
Unit of Measure	ST
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
EAN	4011209696570.0
Quantity in Package	1
Product Code	3727
UPC	887621776657.0

## Description

SIRIUS soft starter S3 106 A, 55 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC  
spring-type terminals