

3RW40472TB05

Industrial automation components

Manufacturer	Siemens
Catalog number	3rw40472tb05
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

ETIM 7	EC000640
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Quantity in Package	1
Packaging Size	MM
ECCN	N
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
EAN	4011209696594.0
Product Code	3727
Comparative Metals Coefficient	01.05.2012
UPC	662643890471.0
Weight	1864 kg
Product ID	3RW4047-2TB05
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	CZ
Product Description	SIRIUS SOFTSTART, WLK. S3, 106A, 75KW/500V, 40 ST., AC 400-600V, AC/DC 24V, ZACISKI SPRĘŻYNOWE, Z TERMISTOROWĄ OCHR. SILNIKÓW,
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Lead titanium zirconium oxide lblREACHCasNo0830; Perfluorobutane sulfonic acid (PFBS) and its salts lblREACHCasNo0211
Unit of Measure	ST
eClass 8	27-37-09-07
eClass Version 9	27-37-09-07
eClass Version 9.1	27-37-09-07
Packaging Length	183,00
Packaging Width	217,00
Packaging Height	220,00
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07

Description

The SIRIUS SOFTSTART is an advanced motor starting device designed for operation in AC 400-600V and AC/DC 24V systems. It offers a maximum current of 106A and a power rating of 75kW at 500V. Equipped with spring terminals and thermistor motor protection, it ensures reliability and safety. The product complies with RoHS and REACH standards, confirming its environmental friendliness. Packaging dimensions are 183x217x220 mm, with a total weight of 1864 g. The country of origin is the Czech Republic.