

## 3RW44223BC46

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 3rw44223bc46                     |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Legacy / discontinued            |

### Technical specification

|                                     |   |
|-------------------------------------|---|
| <b>Product Description</b>          | SIRIUS soft starter Values at 690 V, 40 °C standard: 29 A, 30 kW Inside-delta: only up to 600 V 400-690 V AC, 230 V AC spring-type terminals !!! Phased-out product !!! Successor is SIRIUS 3RW5, Preferred successor type is >>3RW5524-3HA16<< |
| <b>EAN</b>                          | 4011209626843   |
| <b>Country of Origin</b>            | Czech Republic  |
| <b>Article Number</b>               | 3RW44223BC46  |
| <b>Product Family</b>               | 3RW44 soft starters   |
| <b>Product Group</b>                | 3728  |
| <b>Catalog ID</b>                   | CC-IC10   |
| <b>Net Weight</b>                   | 12.024 lb   |
| <b>Packaging Dimensions</b>         | 12.205 x 15.433 x 12.362  |
| <b>Package Size Unit of Measure</b> | Inch  |
| <b>Quantity Unit</b>                | 1 Piece   |
| <b>Packaging Quantity</b>           | 1 pieces  |
| <b>Commodity Code</b>               | 85371098  |
| <b>Current Rating</b>               | 29 A  |
| <b>Voltage Rating</b>               | 690 V, 600 V, 230 V   |
| <b>Power</b>                        | 30 kW   |
| <b>Trip Curve</b>                   | D   |

## Description

SIRIUS soft starter with values at 690 V, 40 °C standard: 29 A, 30 kW. Inside-delta: only up to 600 V 400-690 V AC, 230 V AC with spring-type terminals. Phased-out product, successor is SIRIUS 3RW5, preferred successor type is >>3RW5524-3HA16<<.