

## 3RW44432BC36

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rw44432bc36
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Legacy / discontinued

### Technical specification

<b>Product Description</b>	SIRIUS soft starter Values at 575 V, 50 °C standard: 180 A, 150 hp Inside-delta: 312 A, 300 hp 400-690 V AC, 115 V AC spring-type terminals !!! Phased-out product !!! Successor is SIRIUS 3RW5, Preferred successor type is >>3RW5543-2HA16<<
<b>EAN</b>	4011209627383
<b>Country of Origin</b>	Czech Republic
<b>Product Family</b>	3RW44 soft starters
<b>Catalog ID</b>	CC-IC10
<b>Packaging Dimensions</b>	13.465 x 17.008 x 13.937
<b>Package Size Unit of Measure</b>	Inch
<b>Quantity Unit</b>	1 Piece
<b>Current Rating</b>	180, 312 A
<b>Voltage Rating</b>	575 V, 690 V, 115 V
<b>Article Number</b>	3RW44432BC36
<b>Product Group</b>	3728
<b>Net Weight</b>	24.491 lb
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85371098
<b>Trip Curve</b>	D

## Description

The SIRIUS soft starter 3RW44432BC36 is an advanced device designed for industrial applications. It offers values at 575 V, 50 °C standard: 180 A, 150 hp and in inside-delta configuration: 312 A, 300 hp. It supports voltages from 400 to 690 V AC and 115 V AC. This product is phased out, with its successor being SIRIUS 3RW5, and the preferred successor type is 3RW5543-2HA16. The net weight is 24.491 kg, and the packaging dimensions are 13.465 x 17.008 x 13.937 inches.