

3RW50772TB14

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3rw50772tb14 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|--|
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85371098 |
| Copper Weight | 0 |
| EAN | 4047621061337.0 |
| eClass 6 | 27-37-09-07 |
| eClass 7.1 | 27-37-09-07 |
| eClass 8 | 27-37-09-07 |
| eClass Version 9 | 27-37-09-07 |
| eClass Version 9.1 | 27-37-09-07 |
| Quantity in Package | 1 |
| Packaging Length | 331,00 |
| Packaging Width | 285,00 |
| Packaging Height | 234,00 |
| Product Code | 4980 |
| Comparative Metals Coefficient | 23.09.2019 |
| Weight | 8439 kg |
| Product ID | 3RW5077-2TB14 |
| AL Field | N |
| Compliance | Produkt zgodny z RoHS od: 23.09.2019 |
| Configurable Product | False |
| Country of Origin | CZ |
| ECCN | N |
| ETIM 7 | EC000640 |
| Group Classification Key | R711 |
| List of Characteristics | CC-IC10 |
| Metals Coefficient | LA0----- |
| Packaging Size | MM |
| Product Description | Rozrusznik łagodnego rozruchu SIRIUS 200-480 V 570 A, AC 110-250 V zaciski sprężynowe wejście termistorowe |
| Unit of Measure | ST |

Description

The SIRIUS soft starter operates at 200-480 V with a current rating of 570 A, featuring spring terminals and a thermistor input. Compliant with RoHS since 23.09.2019, it weighs 8439 g and is manufactured in CZ. Packaging dimensions are 331 x 285 x 234 mm.