

### 3RW55562HA16

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rw55562ha16
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
EAN	4047621059372.0
eClass 6	27-37-09-07
eClass 7.1	27-37-09-07
eClass 8	27-37-09-07
eClass Version 9	27-37-09-07
eClass Version 9.1	27-37-09-07
Quantity in Package	1
Packaging Length	600,00
Packaging Width	500,00
Packaging Height	500,00
Product Code	4982
Comparative Metals Coefficient	11.02.2019
Weight	56000 kg
Product ID	3RW5556-2HA16
AL Field	N
Compliance	Produkt zgodny z RoHS od: 11.02.2019
Configurable Product	False
Country of Origin	CZ
ECCN	N
ETIM 7	EC000640
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Packaging Size	MM
Product Description	Rozrusznik łagodnego rozruchu SIRIUS 200-690 V 1100 A, AC 110-250 V zaciski sprężynowe
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one lblREACHCasNo8105; Dicyclohexyl phthalate (DCHP) CAS-Nr. 84-61-7; Dodecamethylcyclohexasiloxane (D6) lblREACHCasNo0976
Unit of Measure	ST

## Description

The SIRIUS soft starter operates at 200-690 V with a current rating of 1100 A and AC 110-250 V spring terminal connections. This product is RoHS compliant since 11.02.2019 and is manufactured in the Czech Republic. It weighs 56 kg, with packaging dimensions of 600 x 500 x 500 mm. EAN: 4047621059372.