

### 3SE2243-0XX

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3se2243-0xx
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.22 kgs
<b>Product ID</b>	3SE2243-0XX
<b>AL Field</b>	N
<b>Aluminium Weight</b>	0
<b>Argent Weight</b>	0
<b>Customs Tariff Code</b>	85365080
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.07.2006
<b>Configurable Product</b>	True
<b>Copper Weight</b>	0
<b>Country of Origin</b>	DE
<b>EAN</b>	4011209534506.0
<b>ECCN</b>	N
<b>REACH</b>	Lead CAS-Nr. 7439-92-1
<b>Unit of Measure</b>	ST
<b>eClass 6</b>	27-27-06-01
<b>eClass 7.1</b>	27-27-06-01
<b>eClass 8</b>	27-27-06-01
<b>eClass Version 9</b>	27-27-06-01
<b>eClass Version 9.1</b>	27-27-06-01
<b>ETIM 7</b>	EC000030
<b>Group Classification Key</b>	R711
<b>List of Characteristics</b>	CC-IC10
<b>Metals Coefficient</b>	LC-----
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	108,00
<b>Packaging Width</b>	67,00
<b>Packaging Height</b>	45,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	WYŁĄCZNIK POZYCYJNY Z OSOBNYM EL. URUCH., W OBUDOWIE Z TWORZYWA, URUCHAMIANY BOCZNIE I CZOŁOWO, STYKI PEŁZAJĄCE 1NO+2NC, SIŁA URUCH. 30N, DOSTAWA BEZ NAPĘDU,
<b>Product Code</b>	3750
<b>Comparative Metals Coefficient</b>	01.07.2006