

### 3SE52340HK211AC4

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3se52340hk211ac4
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Legacy / discontinued

## Technical specification

Weight	0.91 kgs
Product ID	3SE5234-0HK21-1AC4
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.07.2006
Configurable Product	False
Country of Origin	DE
ECCN	N
eClass 6	27-27-06-01
eClass 7.1	27-27-06-01
eClass 8	27-27-06-01
eClass Version 9	27-27-06-01
eClass Version 9.1	27-27-06-01
ETIM 7	EC000030
Group Classification Key	R711
List of Characteristics	CC-IC10
Packaging Length	67,00
Packaging Width	43,00
Packaging Height	148,00
Packaging Size	MM
Comparative Metals Coefficient	01.07.2006
REACH	Lead CAS-Nr. 7439-92-1; Imidazolidine-2-thione (2-imidazoline-2-thiol) lblREACHCasNo4360
Unit of Measure	ST
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85365080
Copper Weight	0
EAN	4011209694736.0
Quantity in Package	1
Product Code	5317
Metals Coefficient	LA-----
Product Description	WYŁĄCZNIK POZYCYJNY SIRIUS, OBUDOWA Z TWORZYWA DO EN50047, 31MM, STYKI MIGOWE 1N0/1NC, Z PRZYŁ. M12, 4-BIEG. MAX. 230V I 4A DŹWIGNIA Z ROLKĄ, DŁUGOŚĆ 21MM, 19MM DŹWIGNIA Z ROLKĄ, ROLKA Z TWORZYWA,

## Description

Position switch Plastic enclosure according to EN 50047, 31 mm 1 NO/1 NC quick action contacts integrated (not replaceable) with M12 connector, 4-pole Pin assignment: Pin1=21, Pin2=22 Pin3=13, Pin4=14 for max. 250 V and 4 A Twist lever, right and/or left switching can be set with plastic roller 19 mm