

### 3SF1234-1QV40-1BA1

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3sf1234-1qv40-1ba1
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.06 kgs
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Imidazolidine-2-thione (2-imidazoline-2-thiol) lblREACHCasNo4360
<b>Unit of Measure</b>	ST
<b>Customs Tariff Code</b>	85365080
<b>EAN</b>	4011209699892.0
<b>Quantity in Package</b>	1
<b>Product Code</b>	3758
<b>Packaging Size</b>	MM
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.03.2017
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>ECCN</b>	N
<b>eClass 6</b>	27-27-06-01
<b>eClass 7.1</b>	27-27-06-01
<b>eClass 8</b>	27-27-06-01
<b>eClass Version 9</b>	27-27-06-01
<b>eClass Version 9.1</b>	27-27-06-01
<b>ETIM 7</b>	EC000030
<b>Group Classification Key</b>	R711
<b>List of Characteristics</b>	CC-IC10
<b>Packaging Length</b>	166,50
<b>Packaging Width</b>	56,00
<b>Packaging Height</b>	77,50
<b>Product Description</b>	WYŁĄCZNIK POZYCYJNY Z OSOBNYM EL. URUCHAMIAJĄCYM, 5 KIER. DOSTĘPU, OBUDOWA Z TWORZYWA DO EN50047, Z ASISAFE, AS-I STATUS:1:F-IN1 I 2:F-IN2, STYKI ZWŁOCZNE 2NC, Z PODŁ. M12, 4-BIEG.,
<b>Comparative Metals Coefficient</b>	01.03.2017
<b>Product ID</b>	3SF1234-1QV40-1BA1